

Specification Sheet

Part Number: 181-43002



Solid Wall Wiring Duct, 4" X 3", Non-Adhesive, PVC, White, 120ft/Carton

Article Number	181-43002
Туре	SD4X3
Color	White (WH)
Features & Benefits	•A temporary film is applied to the covers to protect against scratches and is writable for identification during installation. • Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement. • Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)
Quantity Per	carton
Product Description	HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is

manufactured from high impact, rigid PVC, comes in standard colors of white,

gray and black, and is available in 6 foot lengths.

Short Description	Solid Wall Wiring Duct, 4" X 3", Non-Adhesive, PVC, White, 120ft/Carton
Global Part Name	SD4X3-PVC-WH
Technical Description	Non-Adhesive
Length L (Imperial)	6.0
Length L (Metric)	1.83
Width W (Imperial)	4.0
Width W (Metric)	101.6
Height H (Imperial)	3.07
Height H (Metric)	77.90
Mounting Hole Centers (Imperial)	4.0
Material	Polyvinylchloride (PVC)
Material Shortcut	PVC
Flammability	Self-Extinguishing
Halogen free	No
Operating Temperature (Metric)	+122°F (+50°C)

Reach Complaint(Article 33)	No
ROHS Complaint	Yes
Certification/Specification WEB	EN 50085-1:2005 + A1:2013 UL EN 50085-2-3_1A CSA
UL Recognized (US)	Yes
Package Quantity(Imperial)	120
Package Quantity (Metric)	36.58
Customs Number	3925900000

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions

 $[\]hbox{@}$ 2018 HellermannTyton. All rights reserved.